

What is claimed is:

1 **1.** A method of adding a watermark to a sequence of executable instructions comprising the
2 steps of:

3 receiving the sequence of executable instructions and a key; and
4 modifying the sequence of executable instructions in a manner determined by the key,
5 the sequence being modified such that the usefulness of the sequence for the sequence's
6 intended purpose is not affected thereby.

1 **2.** The method set forth in claim 1 wherein:

2 the step of receiving the sequence of executable instructions further includes receiving
3 a watermark value; and

4 the step of modifying the sequence modifies the sequence so that certain of the
5 instructions therein represent a watermark value.

1 **3.** The method set forth in claim 2 wherein the step of modifying the sequence includes the
2 steps of:

3 using the key to determine locations in the key including modification locations at
4 which the sequence is to be modified; and

5 modifying the sequence at the modification locations such that the locations specified
6 by the key represent the watermark value.

1 **4.** The method set forth in claim 3 wherein the step of modifying the sequence includes the
2 step of:

3 inserting one or more executable instructions at each of the modification locations, the
4 inserted instructions having no effect on any output from the execution of the sequence of
5 instructions.

1 **5.** The method set forth in claim 4 wherein:

2 the instructions at the locations specified by the key represent values of digits of the
3 watermark value.

1 **6.** The method set forth in claim 2 further comprising the step of:

- 2 providing the watermark value to an authenticating entity that authenticates the
3 watermarked code.
- 1 7. The method set forth in claim 2 further comprising the step of:
2 providing the key to the authenticating entity.
- 1 8. The method set forth in claim 1 wherein:
2 the sequence of executable instructions is modified such that when the sequence of
3 executable instructions is executed, execution state is produced which has a property that
4 depends on the key.
5
- 1 9. The method set forth in claim 8 wherein:
2 the execution state is a stack depth graph.
- 1 10. The method set forth in claim 9 wherein:
2 the execution state is output from the execution.
- 1 11. The method set forth in claim 10 wherein:
2 the property is an order of elements in the output.
- 1 12. The method set forth in claim 10 wherein:
2 the property is an additional element in the output.
- 1 13. The method set forth in claim 10 wherein:
2 the property is a class of an element in the output.
- 1 14. The method set forth in claim 10 wherein:
2 the property is a constraint that is satisfied by elements of the output.
- 1 15. The method set forth in claim 8 further comprising the step of:
2 providing a description of the produced execution state to an authenticating entity that
3 authenticates the watermarked code.

1 16. The method set forth in claim 15 further comprising the step of:
2 providing the key to the authenticating entity.

1 17. The method set forth in claim 1 further comprising the step of
2 providing the key to an authenticating entity.

1 17. A method of authenticating a watermarked sequence of executable instructions, the
2 watermark having been produced by modifying the sequence according to a key such that
3 certain of the instructions in the sequence represent a watermark value,
4 the method comprising the steps of:
5 receiving the watermarked sequence or a copy thereof;
6 using the key to locate the certain instructions in the received sequence and read the
7 watermark value; and
8 using the watermark value to determine whether the received sequence is authentic.

1 18. The method of authenticating set forth in claim 17, the method further comprising the step
2 of:
3 receiving another watermark value; and
4 in the step of using the watermark value to determine whether the received sequence is
5 authentic, the watermark value is compared to the other watermark value.

1 19. The method of authenticating set forth in claim 18, the method further comprising the step
2 of:
3 receiving the key.

1 20. A method of authenticating a watermarked sequence of executable instructions, the
2 watermark having been produced by modifying the sequence according to a key such that
3 when the sequence is executed, execution state is produced,
4 the method comprising the steps of:
5 receiving a description of the execution state; and
6 authenticating the watermarked sequence by confirming that the received description
7 describes execution state produced by an execution of the sequence.

1 21. The method set forth in claim 20 further comprising the step of:

2 receiving another description of the execution state, the other description describing
3 execution state produced by the execution of the sequence; and
4 in the step of authenticating, comparing the description and the other description.
5

1 22. The method set forth in claim 21 wherein:

2 the other description is a stack depth graph.

1 23. The method set forth in claim 20 wherein the execution state is output from the execution,
2 the output having a property which can be determined using the key and
3 the method further comprises the steps of:

4 receiving the output from the execution; and
5 the step of authenticating includes the steps of
6 receiving the execution state;
7 employing the key to determine the property; and
8 comparing the determined property with the received description.

1 24. The method set forth in claim 23 wherein:

2 the determined property is an order of elements in the output.

1 25. The method set forth in claim 23 wherein:

2 the determined property is an additional element in the output.

1 26. The method set forth in claim 23 wherein:

2 the determined property is a class of an element in the output.

1 27. The method set forth in claim 23 wherein:

2 the determined property is a constraint that is satisfied by elements of the output.